

MATERIAL SAFETY DATA SHEET (MSDS)

PLASTIC CEMENT
Health: 2
Flammability: 4
Reactivity: 0

SECTION I

EMERGENCY TELEPHONE NO.

TRADE NAME
(if None, Put Chemical) Plastic Cement, (918) 687-5427 (7AM-12M)

CHEMICAL NAME
AND SYNONYMS

MANUFACTURER'S NAME
AND TELEPHONE NO. Camel Tire Care Products

(918) 687-5427

ADDRESS (Number, Street
City, State, Zip Code) P.O. Box 769

Muskogee OK 74402-769

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	%	TLV	PEL	UNITS
Methyl ethyl ketone (78-93-3)	48	200	200	PPM
Toluene (108-88-3)	48	100	200	PPM
Non-hazardous ingredients*	4			

Carcinogenic Ingredients /OSHA/NTP/IARC/None

*Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard (29 CFR 1910,1200).

SECTION III - PHYSICAL DATA

BOILING POINT (°F)	< 175	SPECIFIC GRAVITY (H ₂ O=1)	NE
VAPOR PRESSURE (MM Hg.)	37-71	PERCENT VOLATILE BY VOLUME (%)	< 90
VAPOR DENSITY (AIR=1)	< 1	pH	NE
SOLUBILITY IN WATER	Insoluble	EVAPORATION RATE (Ether=1)	NE <1

APPEARANCE AND ODOR
Liquid; solvent odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	<100 F	FLAMMABLE LIMITS	LEL NE	UEL NE
EXTINGUISHING MEDIA	Carbon dioxide, dry chemical, or foam			
SPECIAL FIRE FIGHTING PROCEDURES	Use water spray or fog to cool fire-exposed containers.			
UNUSUAL FIRE AND EXPLOSION HAZARDS	Vapors can flow to ignition sources and flashback.			

NA - Not Applicable

NE - Not Established

UN - Unavailable

SECTION V - HEALTH HAZARD INFORMATION

TLV

SYMPTOMS/EFFECTS OF OVEREXPOSURE Respiratory irritation, headache, nausea, dizziness, fatigue, confusion, unconsciousness. Central nervous system depression. Prolonged or repeated skin contact may lead to drying, irritation and dermatitis. Possible skin absorption. Eye contact causes burning and irritation.

Symptoms/Effects of Exposure: None

FIRST AID

EYES Immediately flush eyes with large amounts of water for at least 15 minutes while holding the eyelids open. Get prompt medical attention.

SKIN Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists.

INHALATION Move victim to fresh air and restore breathing if necessary. Stay with victim until arrival of emergency medical personnel.

INGESTION Contact local poison control center or physician IMMEDIATELY!

SECTION VI - REACTIVITY DATA

STABILITY Normally Stable.

Avoid heat, sparks, open flame

INCOMPATIBLE MATERIALS Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS Combustion may produce Carbon monoxide, Carbon dioxide

SECTION VII - SPILL OR LEAK PROCEDURES

PROCEDURES Wear personal protective equipment (See Section VIII). Remove heat and ignition sources; ventilate the area; clean up with inert absorbant.

WASTE DISPOSAL METHOD Waste may be burned in an approved incinerator, or dispose of according to Local, State, and Federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY If TLV is exceeded, or for symptoms of overexposure, wear a NIOSH-approved respirator for organic vapors.

EYEWEAR Wear chemical safety goggles.

CLOTHING/GLOVES Wear butyl rubber or other chemical-resistant gloves and apron or coveralls as needed to prevent skin contact.

VENTILATION Local exhaust may be necessary under some handling/use conditions.


Specific needs should be addressed by supervisory or health/safety personnel.

SECTION IX - SPECIAL PRECAUTIONS

FLAMMABLE LIQUID. Store in closed container in cool, well-ventilated area.

APPROVAL

NAME



TITLE

Director of MFG. December 10, 1987

DATE