ITEM: 3KB83 - Remover Adhesive 24 Oz 18.4 oz Net

PICK REQ: 1215608769

MATERIAL SAFETY DATA SHEET (MSDS)

Associated Grainger Item: 3KB83 - Remover Adhesive 24 Oz 18.4 oz Net

3M

MATERIAL SAFETY DATA SHEET

3M(TM) ADHESIVE REMOVER 6040 / 6041 (AFROSOL)

09/13/2005

MATERIAL SAFETY DATA SHEET

COPYRIGHT, 2005, 3M COMPANY. ALL RIGHTS RESERVED. COPYING AND/OR DOWNLOADING OF THIS INFORMATION FOR THE FURPOSE OF PROPERLY JIILIZING 3M PRODUCTS IS ALLOWED PROVIDED THAT:

(1) THE INFORMATION IS COPIED IN FULL WITH NO CHANGES UNLESS PRIOR WRITTEN AGREEMENT IS OBTAINED FROM 3M, AND

(2) NEITHER THE COPY NOR THE CRIGINAL IS RESOLD OR OTHERWISE DISTRIBUTED WITH THE INTENTION OF EARNING A PROFIT THEREON.

- SECTION 1: PRODUCT AND COMPANY IDENTIFICATION -

PRODUCT NAME: 3M(TM) ADHESIVE REMOVER 6040 / 6041 (AEROSOL)

MANUFACTURER: 3M

DIVISION: INDUSTRIAL ADHESTVES AND TAPES

3M CENTER

ST. PAUL, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 OR (651) 737-6501 (24 HOURS)

ISSUE DATE: 09/13/2005 SUPERCEDES DATE: 12/14/2004 DOCUMENT GROUP: 08-6485-0

PRODUCT USE:

SPECIFIC USE: ADHESIVE REMOVER

- SECTION 2: INGREDIENIS -

INCREDIENT

C.A.S. NO.

% BY WI

CITRUS EXTRACT

8028-48-6

80 - 90

PROPANE

74-98-6

10 - 20

SECTION 3: HAZARDS IDENTIFICATION —

3.1 EMERGENCY OVERVIEW:

ODOR, COLOR, GRADE: CLEAR, PALE YELLOW, SWEET ODOR

GENERAL PHYSICAL FORM: GAS

IMMEDIATE HEALTH, PHYSICAL, AND ENVIRONMENTAL HAZARDS: CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY SUILD RESSURE AND EXPLODE. EXTREMELY FLAMMABLE LIQUID AND VAPOR. AEROSOL CONTAINER CONTAINS FLAMMABLE MATERIAL UNDER PRESSURE. MAY CAUSE ALLERSIC SKIN REACTION.

3.2 POTENTIAL HEALTH EFFECTS:

EYE CONTACT .

EYE COMIACI: MODERATE EYE IRRITATION: SIGNS/SYMPICMS MAY INCLUDE REDNESS, SMELLING, PAIN, TEARING, AND BLURRED CR HAZY VISION.

SKIN CONTACT:

MODERATE SKIN IRRITATION: SIGNS/SYMPTOMS MAY INCLUDE LOCALIZED REDNESS, SWELLING, ITCHING, AND

PROLONGED OR REPEATED EXPOSURE MAY CAUSE: ALLERGIC SKIN REACTION (NON-PHOTO INDUCED): SIGNS/SYMPTOMS MAY INCLUDE REDNESS, SWELLING, BLISTERING, AND ITCHING.

INHALATION:
RESPIRATORY TRACT IRRITATION:
SIGNS/SYMPTOMS MAY INCLUDE CCUSH, SNEHZING, NASAL DISCHARGE, HEADACHE, HOARSENESS, AND NOSE AND THEOAT PAIN.

INTENTIONAL CONCENTRATION AND INHALATION MAY BE HARMFUL OR FATAL.

GASTROINTESTINAL IRRITATION: SIGNS/SYMPTOMS MAY INCLUDE AEDOMINAL PAIN, STOMACH UPSET, NAUSEA, VOMITING AND DIARRHEA.

3.3 POTENTIAL ENVIRONMENTAL EFFECTS: CHEMICAL ANALYSIS OF 3M CITRUS BASE ADMESTIVE REMOVER YIELDED THE FOLLOWING DATA:

CHLORIDE: <10 PPM FILORIDE: <1 PPM SULFUR: <4 PPM TOTAL HALOGEN: <10 PPM.

- SECTION 4: FIRST AID MEASURES -

4.1 FIRST AID PROCEDURES: THE FOLLOWING FIRST AID FECOMMENDATIONS ARE BASED ON AN ASSUMPTION THAT APPROPRIATE PERSONAL AND INDUSTRIAL HYGIEVE PRACTICES AFF FOLLOWED

MSDS: B0893

444444444444

EYE CONTACT: FLUSH EYES WITH LARGE ANCUNIS OF WATER. IF SIGNS/SYMPTOMS PERSIST, GET MEDICAL ATTEMION.

REMOVE CONTAMBIATED CLOTHING AND SHOES, IMMEDIATELY FLUSH SKIN WITH LARGE AMOUNTS OF WATER, GET MEDICAL ATTENTION. WASH CONTAMINATED CLOTHING AND CLEAN SHOES BEFORE REUSE.

INHALATION: REMOVE PERSON TO FRESH AIR. IF SIGNS/SYMPTOMS DEVELOP, CET MEDICAL ATTENTION.

IF SWALLOWED!

TO NOT INDUCE VOMITING UNLESS INSTRUCTED TO DO SO BY MEDICAL PERSONNEL.

GIVE VICTIM TWO GLASSES OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON. GET MEDICAL ATTENTION.

- SECTION 5: FIRE FIGHTING MEASURES ---

5.1 FLAMMABLE PROFERRIES:

AUTOIGNITION TEMPERATURE: NO DATA AVAILABLE

FLASH POINT: -50.00 DEG. F

FLAMMABLE LIMITS - LEL: 2.1 % VOLUME (DETAILS: CONDITIONS: PROPANE)
FLAMMABLE LIMITS - UEL: 9.5 % VOLUME (DETAILS: CONDITIONS: PROPANE)

5.2 EXTINGUISHING MEDIA: USE FIRE EXTINGUISHERS WITH CLASS B EXTINGUISHING AGENIS (E.G., DRY CHEMICAL, CAREON DIOXIDE).

5.3 PROTECTION OF FIRE PIGHTERS:

SPECIAL FIRE FIGHTING PROCEDURES MERR FULL PROTECTIVE BOUIPMENT (BUNKER GEAR) AND A SELF-CONTAINED BREATHING APPARATUS (SCEA).

UNUSUAL FIRE AND EXPLOSION HAZARDS: CLOSED CONTAINERS EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE AND EXPLODE. EXTREMELY FLAMMABLE LIQUID AND VAPOR. ABROSOL CONTAINER CONTAINS FLAMMABLE MATERIAL UNDER PRESSURE.

NOTE: SEE STABILITY AND REACTIVITY (SECTION 10: FOR HAZARDOUS COMBUSTION AND THERMAL DECOMPOSITION INFORMATION.

-- SECTION 6: ACCIDENTAL RELEASE MEASURES --

ACCIDENTAL RELEASE MEASURES:
REFER TO OTHER SECTIONS OF THIS MSDS FOR INFORMATION REGARDING PHYSICAL AND HEALTH HAZARDS, ESSPERATORY PROTECTION, VENTUATION, AND PERSONAL PROTECTIVE EQUIPMENT. CALL 3M-HELPS LINE (1-800-364-3577) FOR MORE INFORMATION ON HANDLING AND MANAGING THE SPILL. EVACUATE UNPROTECTED AND UNITRAINED PERSONNEL FROM HAZARD AREA. THE SPILL SHOULD BE CLEANED UP BY CUALIFIED PERSONNEL. REMOVE ALL IGNITION SOURCES SUCH AS FLAMES, SNOK MY MATERIALS, AND ELECTRICAL SPARE SOURCES. USE ONLY NON-SPARGUED TOOLS. "ANDIHATE THE AREA WITH FRESH AIR. IF FOSSIBLE, SEAL LEAKING CONTAINER. PLACE LEAKING CONTAINERS IN A WELL-VENTILATED AREA, PREFERABLY AN OPERATING EXHAUST HOOD, OR IF INCCESSARY OUTDOORS ON AN IMPERAMEABLE SURFACE UNTIL APPROPRIATE PACKAGING FOR THE LEAKING CONTAINER OR ITS CONTAINER SHAUST HOOD, OR IF INCCESSARY OUTDOORS ON AN IMPERAMEABLE SURFACE UNTIL APPROPRIATE PACKAGING FOR THE LEAKING CONTAINER OR ITS CONTAINED IN A WALL-VENTILATED AREA, PREFERABLY AN OPERATING EXHAUST HOOD, OR IF INDUSTRIES IN A WELL-VENTILATED AREA, PREFERABLY AN OPERATING EXHAUST HOOD, OR IF INDUSTRIES IN A WELL-VENTILATED AREA, PREFERABLY AN OPERATING EXHAUST HOOD, OR IF NECESSARY OUTDOORS. DISPOSE OF COLLECTED MATERIAL AS SCON AS FOSSIBLE. CCIDENTAL RELEASE MEASURES

IN THE EVENT OF A RELEASE OF THIS MATERIAL, THE USER SHOULD DEIERMINE IF THE RELEASE QUALIFIES AS REPORTABLE ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS.

SECTION 7: HANDLING AND STORAGE ----

7.1 HANDLING:
DO NOT EAT, DRIDK OR SMOFE WHEN USING THIS PRODUCT. WASH EXCOUNT AREAS
THOROUGHLY WITH SOAP AND WEITER. KEEP AWEY FROM HEAT, SPARKS OFEN FLYME,
PILOT LIGHTS AND OTHER SCURCES OF IGNITION. ANODD EYE CONTAIN WITH VAPORS,
MISTS, OR SPRAY. KEEP OUT OF THE REACH OF CHILDREN. VAPORS MAY IGNITE
EXPLOSIVELY. MAY CAUSE FLASH FIRE. PREVENT BUILD-UP OF VAPORS - OPEN ALL
WINDOWS AND DOORS. MAINTAIN VAPOR CONCENTRATIONS BELOW REOXMENDED EXPOSURE
LIMITS. USE ONLY WITH CROSS-VENTILATION. WITHOUT APPORTATE THE DEPOSURE
LIMITS. USE ONLY WITH CROSS-VENTILATION. WITHOUT APPORTATE THIS IN LOW-LYING AREAS. KEEP AWEM FROM HEAT, SPARKS, AND OPEN
FLAME. DO NOT SMOKE OR IGNITE MATCHES, LIGHTERS, ETC.

STORE AWAY FROM ACIIS. STORE AWAY FROM HEAT. STORE OUT OF DURECT SUNLIGHT.
KEEP CONTAINER IN WELL-VENTILATED AREA.

- SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION -

8.1 ENSINEERING CONTROLS:

USE WITH APPROPRIATE LOCAL EXHAUST VENTILATION. PROVIDE APPROPRIATE LOCAL EXHAUST VENTILATION ON OFEN CONTAINERS. USE WITH FUNCTIONING SERAY BOOTH OR LOCAL EXHAUST. DO NOT USE IN A CONFINED AREA OR AREAS WITH LITTLE OR NO AIR MOVEMENT, USE GENERAL DILUTION VENTILATION AID/OR LOCAL EXHAUST VENTILATION TO CONTROL AIRBORNE EXPOSURES TO BELOW COUPATIONAL EXPOSURES LIVITS AND/OR CONTROL MIST, VAPOR, OR SPRAY IF VENTILATION IS NOT ADEQUATE, USE RESPIRATORY FROMEDTION EQUIPMENT. DO NOT USE IN A CONTINED AREA OR AFEAS WITH LITTLE OR NO AIR MOVEMENT. IF EXHAUST VENTILATION IS NOT ADEQUATE, USE APPROPRIATE RESPIRATORY FROMEDTION. PROVIDE VENTILATION AND XMITE TO CONTROL APPROPRIATE RESPIRATORY FROMEDTION. PROVIDE VENTILATION AND XMITE TO CONTROL SPRAY OR MIST. 8 1 ENGINEERING CONTROLS.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE):

8.2.1 EYE/FACE PROTECTION: AVOID EYE CONTACT WITH VAPORS, MISTS, OR SPRAY

THE FOLLOWING EYE PROTECTION(S) ARE RECOMMENDED: SAFETY GLASSES WITH SIDE SHIELDS.

8.2.2 SKIN PROTECTION:

AVOID SKIN CONTACT. SELECT AND USE GLOVES AND/OR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT BASED ON THE RESULTS OF AN EXPOSURE ASSESSMENT, CONSULT WITH YOUR GLOVE AND/OR PROTECTIVE CLOTHING MANUFACTURER FOR SELECTION OF APPROPRIATE COMPATIBLE MATERIALS.

8.2.3 RESPIRATORY PROTECTION:
AVOID BREATHING OF VAPORS, MISIS OR SPRAY.
SELECT CNE OF THE FOLLOWING NICSH APPROVED RESPIRATORS BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS AND IN ACCORDANCE WITH OSHA REGULATIONS:
HALF FACEPIECE AIR-PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGES.
CONSULT THE CURRENT 3M RESPIRATORY SELECTION GUIDE FOR ADDITIONAL INFORMATION OR CALL 1-800-243-4630 FOR 3M TECHNICAL ASSISTANCE.

8.2.4 prevention of swallowing: do not fat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

INGREDIENT AUTHORITY TYPE LIMIT

ADDITIONAL INFORMATION

PROPANE PROPANE

ACGTH

TWA

1000 PPM 1000 PPM

TWA

TABLE Z-1

OSHA SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTA", INDUSTRIAL HYGIENISTS

CMRG: CHEMICAL MANUFACTURER RECOMMENDED GUIDELINE

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

AMERICAN INDUSTRIAL HYGIENE ASSOCIATION WOR PLACE ENVIRONMENTAL EXPOSURE LEVEL (WEEL)

- SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

ODOR, COLOR, GRADE: CLEAR, PALE YELLOW, SWEET ODOR

GENERAL PHYSICAL FORM: GAS

AUTOIGNITION TEMPERATURE: NO DATA AVAILABLE

FLASH POINT: -50.00 DEG. F

FLAMMABLE LIMITS - LEL: 2.1 % VOLUME (DETAILS: CONDITIONS: PROPANE)
FLAMMABLE LIMITS - UEL: 9.5 % VOLUME (DETAILS: CONDITIONS: PROPANE)

VAPOR DENSITY: NOT APPLICABLE

VAPOR PRESSURE: 23 MMHg (@ 20 DEG. C) (DETAILS: COMPOSITE VAPOR PRESSURE (CALCULATED))

SPECIFIC GRAVITY: 0.793 (REF SID: WATER=1

pH: NOT APPLICABLE

MELTING POINT: NO DATA AVAILABLE

SOLUBILITY IN WATER: NIL

EVAPORATION RATE: NO DATA AVAILABLE

VOLATILE ORGANIC COMPOUNDS: APPROXIMATELY 100 % (TEST METHOD: CALCULATED SCAQMD RULE 443.1)

PERCENT VOLATILE: APPROXIMATELY 100 % WEIGHT

VOC LESS H20 & EXEMPT SOLVENTS: APPROXIMATELY 100 % (TEST METHOD: CALCULATED SCAQMD RULE 443.1)

VISCOSTTY: NOT APPLICABLE

- SECTION 10: STABILITY AND REACTIVITY -

STABILITY: STABLE.

MATERIALS AND CONDITIONS TO AVOID: HEAT

HAZARDOUS POLYMERIZATION: HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

SUBSTANCE

CONDITION

ALDEHYDES

DURING COMBUSTION

HYDROCARBONS

DURING COMBUSTION DURING COMBUSTION

CARBON MONOXIDE CARBON DIOXIDE

DURING COMBUSTION

KETONES

NOT SPECIFIED

- SECTION 11: TOXICOLOGICAL INFORMATION

PLEASE CONTACT THE ADDRESS LISTED IN SECTION 1 OF THIS MSDS FOR TOXICOLOGICAL INFORMATION ON THIS WATERIAL AND/OR ITS COMPONENTS.

- SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: NOT DETERMINED.

CHEMICAL FATE INFORMATION: NOT DETERMINED.

```
- SECTION 13: DISPOSAL CONSIDERATIONS --
```

WASTE DISPOSAL MEHOD: INCINERATE IN A PERMITTED HAZARDOUS WASTE INCINERATOR. AS A DISPOSAL ALTERNALIVE, DISPOSE OF WASTE PRODUCT IN A PERMITTED HAZARDOUS WASTE

FACILITY.
THE FACILITY SHOULD BE EQUIPPED TO HANDLE GASEOUS WASTE.
RECYCLE EMPTY AEROSOL CONTAINERS WHERE AVAILABLE.

EPA HAZARDOUS WASTE NUMBER (RCRA): DOOL (IGNITABLE)

SINCE REGULATIONS VARY, CONSULT APPLICABLE REGULATIONS OR AUTHORITIES BEFOR

-- SECTION 14: TRANSPORT INFORMATION ---

ID NUMBER(S): 62-4667-2928-2, 62-4667-2930-8, 62-466"-2935-7, 62-4667-4930-6, 62-4667-4932-2, 62-4667-4935-5

PLEASE CONTACT THE EMERGENCY NUMBERS LISTED IN SECTION 1 OF THIS MSDS FOR TRANSPORTATION INFORMATION FOR THIS MATERIAL.

- SECTION 15: REGULATORY INFORMATION --

US FEDERAL REGULATIONS: (XNTACT 3M FOR MORE INFORMATION).

311/312 HAZARD CATEGORIES: FIRE HAZARD: YES PRESSURE HAZARD: YES REACTIVITY HAZARD: NO IMMEDIATE HAZARD: YES DELAYED HAZARD: NO

STATE REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

CHEMICAL INVENTORIES:
THE COMPCNENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE CHEMICAL NOTIFICATION REQUIREMENTS OF TSCA

ALL APPLICABLE CHEMICAL INGREDIENTS IN THIS MATERIAL ARE LISTED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICAL SUBSTANCES (HINEGS), OR ARE EXEMPT POLYMERS WHOSE MONOMERS ARE LISTED ON EINECS.

CONTACT 3M FOR MORE INFORMATION.

INTERNATIONAL REGULATIONS: CONTACT 3M FOR MORE INFORMATION.

THIS MSDS HAS BEEN PREPARED TO MEET THE U.S. OSHA HAZZED COMMUNICATION STANDARD, 29 CFR 1910.1200.

- SECTION 16: OTHER INFORMATION

NFPA HAZARD CLASSIFICATION:

HEALTH FLAMMABILITY SPECIAL HAZARDS NONE

AEROSOL STORAGE CODE: 2

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD RAITNGS ARE DESIGNED FOR USE BY EMERGENCY RESPONSE PERSONNEL TO ADDRESS THE HAZARDS THAT ARE PRESENTED BY SHORT-TERM, ACUTE EXPOSURE TO A MATERIAL UNDER CONDITIONS OF FIRE, SPILL, OR SIMILAR EMERGENCIES: HAZARD RATINGS AFE PRIMARILY HASED ON THE INHERIAL PHYSICAL AND TOXIC PROPERTIES OF THE MATERIAL BUT ALSO INCLUDE THE TOXIC PROPERTIES OF COMBUSTION OR DECOMPOSITION PRODUCTS THAT ARE HYGAN TO BE GENERATED IN SIGNIFICANT QUANTITIES.

REVISION CHANGES: COPYRIGHT WAS MODIFIED.

SECTION 3: IMMEDIATE PHYSICAL HAZARD(S) WAS MODIFIED.

SECTION 3: FOLENTIAL EFFECTS FROM SKIN CONTACT INFORMATION WAS MODIFIED.

SECTION 3: POTENTIAL EFFECTS FROM INHALATION INFORMATION WAS MODIFIED.

SECTION 3: POTENTIAL EFFECTS FROM INGESTION INFORMATION WAS MODIFIED.

SECTION 5: UNUSUAL FIRE AND EXPLOSION HAZARD INFORMATION WAS MODIFIED

SECTION 6: RELEASE MEASURES INFORMATION WAS MODIFIED.

SECTION 7: HANDLING INFORMATION WAS MODIFIED.

SECTION 7: STORAGE INFORMATION WAS MODIFIED.

SECTION 8: ENGINEERING CONTROLS INFORMATION WAS MODIFIED.

SECTION 8: EYE/FACE PROTECTION PERASE WAS MODIFIED.

SECTION 13: WASTE DISPOSAL METHOD INFORMATION WAS MODIFIED.

SECTION 4:

FIRST AID FOR INGESTION (SWALLOWING) - DECONTAVINATION - VAS MODIFIED.

FIRST AID FOR INGESTION (SWALLOWING) - MEDICAL ASSISTANCE - WAS MODIFIED.

SECTION 15: 311/312 DELAYED HAZARD SCORE WAS MODIFIED.

SECTION 3: IMMEDIATE SKIN HAZARD(S) WAS ADDED.

SECTION 9: VAPOR PRESSURE VALUE WAS ADDED.

SECTION 3: OTHER POTENTIAL HEALTH EFFECTS HEADING WAS DELETED.

SECTION 3: IMMEDIATE OTHER HAZARD(S) WAS DELETED.

SECTION 3: OTHER HEALTH EFFECTS INFORMATION WAS DELETED.

DISCLAIMER

DISCLAURER:
THE INFORMATION IN THIS MATERIAL SAFETY DATA SHEET (MYDS) IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR FURPOSE OR COURSE OF PERFORMINGE OR USAGE OF TRADE

USER IS RESPONSIBLE FOR DETERMINING WHETHER THE 3M PRODUCT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION. GIVEN THE VARIETY OF FACTORS THAT CAN AFFECT THE USE AND APPLICATION OF A 3M PRODUCT, SOME OF WHICH ARE UNIQUELY WITHIN THE USER'S KNOWLEDGE AND CONTROL, IT IS ESSENTIAL THAT THE USER EVALUATE THE 3M PRODUCT TO DETERMINE WHETHER IT IS FIT FOR A PARTICULAR PURPOSE AND SUITABLE FOR USER'S METHOD OF USE OR APPLICATION.

3M PROVIDES INFORMATION IN ELECTRONIC FORM AS A SERVICE TO ITS CUSTOMERS, DUE TO THE REMOTE POSSIBILITY THAT ELECTRONIC TRANSFER MAY HAVE RESULTED IN ERRORS, OMISSIONS OR ALTERATIONS IN THIS INFORMATION, 3M MAKES NO REPRESENTATIONS AS TO ITS COMPLETENESS OR ALCURACY. IN ADDITION, INFORMATION OBTAINED FROM A DATABLES MAY NOT BE AS CURRENT AS THE INFORMATION IN THE MSDS AVAILABLE DIRECTLY FROM 3M.

3M MSDSS ARE AVAILABLE AT WWW.3M.COM