

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number

955

Product name

Anti-Static Spray

Effective date

14-Nov-2007

Company information

Sprayway, Inc.

484 Vista Ave. Addison, IL 60101 United States

Company phone

General Assistance 630-543-7600

Emergency telephone US

800-424-9300

Emergency telephone outside US

703-527-3887

Supersedes date

17-Aug-2007

2. Hazards Identification

Emergency overview

CONTENTS UNDER PRESSURE.

Aerosol. Pressurized container may explode when exposed to heat or flame.

Irritating to eyes. Can cause adverse reproductive effects. Prolonged exposure may

cause chronic effects.

OSHA regulatory status

This product is considered hazardous under 29 CFR 1910.1200 (Hazard

Communication).

Potential health effects

Eyes

Causes eye irritation.

Skin Prolonged or rep

Prolonged or repeated contact can result in defatting and drying of the skin which may

result in skin irritation and dermatitis (rash).

Inhalation

Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion

Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Target organs

Blood. Central nervous system. Liver. Respiratory system.

Chronic effects

Unconsciousness. Sterility. Liver injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage. Can cause adverse reproductive effects. Pregnant women or women of child-bearing age

should not be exposed to this product.

Signs and symptoms

Discomfort in the chest. Narcosis. Cyanosis. Liver enlargement. Jaundice. Defatting of the

skin. Irritation, Birth defects. Sterility.

3. Composition / Information on Ingredients

| Components | CAS# | Percent |
|--|----------|---------|
| Ethyl Alcohol | 64-17-5 | 70 - 80 |
| n-Butane | 106-97-8 | 15 - 20 |
| Propane | 74-98-6 | 5 - 8 |
| Non-hazardous and other components below reportable levels | | 0.1 - 1 |

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Get medical attention if irritation develops or persists.

Immediately take off all contaminated clothing. Wash off with warm water and soap. Get

Skin contact Immediately take off all contaminated clothing. W medical attention if irritation develops or persists.

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Ingestion

Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician General advice Symptoms may be delayed.

Call a physician if symptoms develop or persist.

5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition

sources and flash back.

Extinguishing media

Suitable extinguishing media

Foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters

Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor possible withdraw from area and let fire hum.

nozzles; if this is impossible, withdraw from area and let fire burn.

Specific hazards

Fire may produce irritating, corrosive and/or toxic gases.

6. Accidental Release Measures

Personal precautions

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated

surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Level 2 Aerosol.

74-98-6

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.

Not established

8. Exposure Controls / Personal Protection

Exposure limits

| ACGIH | ļ |
|-------|---|
|-------|---|

| Components | CAS# | TWA | STEL | Ceiling |
|---------------|----------|----------|-----------------|-----------------|
| Ethyl Alcohol | 64-17-5 | 1000 ppm | Not established | Not established |
| n-Butane | 106-97-8 | 1000 ppm | Not established | Not established |
| Propane | 74-98-6 | 1000 ppm | Not established | Not established |
| OSHA | | | | |
| Components | CAS# | TWA | STEL | Ceiling |
| Ethyl Alcohol | 64-17-5 | 1000 ppm | Not established | Not established |

1000 ppm

Not established

Propane

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye / face protectionWear chemical goggles. **Skin protection**Protective gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

General hygeine considerations When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Handle in

accordance with good industrial hygiene and safety practice.

9. Physical & Chemical Properties

Appearance Compressed liquefied gas.

Color clear colorless
Odor Characteristic.
Physical state Liquid.

Form Aerosol.

Flammability (HOC) 29.51 kJ/g estimated

Flash back No

Pressure 43 - 53 psig @70F

Solubility Negligible

Flash point -156 °F (-104.4 °C) estimated Boiling point 127.4 °F (52.8 °C) estimated

Specific gravity 0.7163 pH Not applicable

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition. Stable at normal conditions.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Isocyanates.

Hazardous decomposition products May include oxides of nitrogen.

11. Toxicological Information

Acute effects Acute LD50: 2016 mg/kg estimated, Rat, Oral

Acute LC50: 168 mg/l/4h estimated, Rat, Inhalation

Sensitization Not expected to be hazardous by OSHA criteria.

Local effects Liver toxicity. Blood disorder may occur after ingestion. Irritating to eyes. Components of

the product may be absorbed into the body through the skin.

Chronic effects Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous

system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury.

Prolonged exposure may cause chronic effects.

Subchronic effects Blood disorder may occur after prolonged inhalation. Blood disorder may occur after

prolonged skin contact.

Neurological effects Hazardous by OSHA criteria.

Mutagenicity Not expected to be hazardous by OSHA criteria.

Reproductive effects Hazardous by OSHA criteria. Possible reproductive hazard. Can cause adverse

reproductive effects - such as birth defects, miscarriages, and infertility.

Teratogenicity Not expected to be hazardous by OSHA criteria.

Epidemiology Hazardous by OSHA criteria. **Further information** Symptoms may be delayed.

12. Ecological Information

Ecotoxicity LC50 17281 mg/L estimated, Fish, 96.00 Hours,

EC50 12306 mg/L estimated, Daphnia, 48.00 Hours,

Components of this product have been identified as having potential environmental

concerns.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructions

Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name

Consumer commodity

Hazard class

ORM-D

Subsidiary hazard class

None

Additional information:

Packaging exceptions Packaging non bulk

Packaging bulk

156, 306

156, 306 None

IMDG

Basic shipping requirements:

Proper shipping name

AEROSOLS, flammable

Hazard class UN number 2.1 1950

Additional information:

Packaging exceptions

LTD QTY

Item

5F

Labels required

2.1

Transport Category

2

IATA

Basic shipping requirements:

Proper shipping name

Aerosols, flammable

Hazard class UN number 2.1 1950

Additional information:

Packaging exceptions LTD QTY





15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous

Yes

chemical

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely hazardous substance

No

Section 311 hazardous chemical Yes

Inventory status

| Country(s) or region | Inventory name | On inventory (y | es/no)* |
|-----------------------------|--|-----------------|---------|
| China | Inventory of Existing Chemical Substances in China (IECSC) | | No |
| Europe | European Inventory of New and Existing Chemicals (EINECS) | | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | | No |
| Korea | Existing Chemicals List (ECL) | | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | | Yes |

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

 Ethyl Alcohol
 64-17-5
 Present

 n-Butane
 106-97-8
 Present

 Propane
 74-98-6
 Present

16. Other Information

HMIS® ratings Health: 1*

Flammability: 3

Physical hazard: 0

Prepared by Regulatory Compliance

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

Issue date 14-Nov-2007