MSDS No.: GR018

I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY

Address: 600 RADIATOR ROAD

City, ST Zip: INDIAN TRAIL, NC 28079

Country: USA

Contact: Robert Geer

Information Telephone Number: 704-684--181 1
Emergency Contact: RMPDC (877-740-5015)
Emergency Telephone Number: 303-623-5716

Emergency Restrictions:

Product Name: LIQUID WRENCH WHITE LTHIUM GREASE

MSDS No.: GR018

Issue Date: 01/14/2014
Supersedes Date: Not Available

II. Hazards Identification:

EMERGENCY OVERVIEW

CAUTION: HARMFUL IF SWALLOWED. EYE AND SKIN IRRITANT

OSHA Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Health Effects

Route(s) of Entry:

Eyes, skin, inhalation and ingestion

Health Hazards (Acute and Chronic):

Exposure to vapors generated at high temperatures may cause respiratory irration.

Signs and Symptoms:

None known

Medical Conditions Generally Aggravated by Exposure:

None known

Other Health Warnings:

Vomiting and subsequent aspiration of the product into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

Potential Environmental Effects

Not Available

III. Composition/Information on Ingredients:

Chemical Name	CAS No.	% Range	Trade Secret
Naphthenic Petroleum Distillate	64742-52-5	60.0 - 100.0	
Titanium dioxide	13463-67-7	1.0 - 5.0	
Zinc oxide, fume	13141-3-2	1.0 - 5.0	

IV. First Aid Measures:

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash skin with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Remove and isolate contaminated clothing. Launder contaminated clothing before reuse.

Inhalation: Move victim to fresh air. If breathing becomes difficult, get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

MSDS No.: GR018
Note to Physicians:

N/D

V. Fire Fighting Measures:

Suitable Extinguishing Media:

Carbon dioxide, Foam, Water fog and Dry Chemical

Unsuitable Extinguishing Media:

Class A type extinguishers.

Products of Combustion:

Oxides of: Carbon

Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes.

VI. Accidental Release Measures:

Personal Precautions:

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental Precautions:

Keep product out of sewers and watercourses.

Methods for Containment:

Will not flow.

Methods for Cleanup:

Using a scoop, place contaminated material into an approved chemical waste container.

Other Information:

Notify authorities if product has entered or may enter sewer, watercourses or extensive land areas.

VII. Handling and Storage:

Handling Precautions:

Ventilate well, avoid breathing vapors. Keep away from heat, sparks and open flame. Slip hazard. Avoid spilling, skin and eye contact. Keep away from children and animals. Keep lid closed when not in use.

Storage Precautions:

Store separate from strong acids and oxidizers. Keep away from heat, spark and open flame.

VIII. Exposure Controls/Personal Protection:

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits	
Naphthenic Petroleum Distillate	5 mg/m3	5 mg/m3	Not Available	
Zinc oxide, fume	5 mg/m3	5 mg/m3	Not Available	
Titanium dioxide	15 mg/m3	10 mg/m3	Not Available	

Engineering Controls:

See Section above for applicable exposure limits. Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

Personal Protective Equipment:

For prolonged exposure wear protective goggles, gloves, and apron.

MSDS No.: GR018

IX. Physical and Chemical Properties:

Boiling Point: N/D Boiling Range: N/D

Solubility In Water: Insoluble in water

Flash Point: 435°F

Odor Threshold: N/D

Vapor Density (AIR = 1): > 5

pH Range: N/A

Decomposition Temp: N/D
Lower Explosive Limit: N/D
Specific Gravity (H20 = 1): 0.89

Other Information: N/D

Melting Point: N/D Freezing Point: N/D

Evaporation Rate (Butyl Acetate = 1): < 0.01

Flash Point Method: COC

Appearance and Odor: White grease with mild petroleum odor

Vapor Pressure (mm Hg.): < 0.1 mmHg @ 20°C

Partition Coefficient: N/C
Auto-Ignition Temp: N/D
Upper Explosive Limit: N/D

X. Stability and Reactivity:

Stability:

Normally Stable

Conditions to Avoid:

Avoid contact with acids and oxidizing substances

Incompatible Materials:

Acids and oxidizers

Hazardous Decomposition Products:

Oxides of carbon

Possibility of Hazardous Reactions:

Will not occur

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in a recycling center when empty. Before offering for recycling, empty the can by using the product according to the label. Do not dump into sewers, on the ground, or into any body of water. Dispose of unused product in accordance with all local, state government and federal laws and regulations

XIV. Transport Information:

Shipping Name: Not DOT Regulated

DOT Hazard Class: Not Regula

UN/NA#: Not Available
Transportation Information:

DOT Subsidiary Hazard Class: Not Available

Packing Group: Not Available

MSDS No.: GR018

DOT Shipping Name: Not DOT regulated.

DOT Hazard Class: None

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for all shipping purposes.

ICAO/IATA (US): Not regulated

International:

ICAO/IATA: Not regulated

IMDG: Not regulated

XV. Regulatory Information:

Sara 313 Reportable Chemicals:

Zinc Oxide 1314-13-2 (Zinc compound)

USA TSCA: All components of this material are either exempt or listed on the US TSCA Inventory.

State RTK Chemicals: Zinc Oxide 1314-13-2 Titanium Dioxide 13463-67

Titanium Dioxide 13463	-67-7				
XVI. Other Inform	ation.				
Chemical State: Chemical Type: Hazard Category: X Acute	Liquid Pure Chronic Pressure	Gas Mixture Fire Reactive	Solid	Health Fleastivity 0 Special	1-1-0
Additional Manufacture Do not used in confine may cause further dar CHILDREN AND ANIM	ed area without prop nage in case of spla	per ventilation. Contactions into eye. KEEP A	ct lenses WAY FROM		1-1-0

N/E: Not Established N/D: Not Determined N/A: Not Applicable N/AV: Not Available

Additional Product Information:

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.

Pers. Protection