# **Sprayway**®

### **MATERIAL SAFETY DATA SHEET**

1. Product and Company Identification

Product number 955

Product name Anti-Static Spray

Effective date 14-Nov-2007
Company information Sprayway, Inc.

484 Vista Ave.

Addison, IL 60101 United States

Company phone General Assistance 630-543-7600

Emergency telephone US 800-424-9300 Emergency telephone outside US 703-527-3887 Supersedes date 17-Aug-2007

2. Hazards Identification

Emergency overview CONTENTS UNDER PRESSURE.

Aerosol. Pressurized container may explode when exposed to heat or flame.

Irritating to eyes. Can cause adverse reproductive effects. Prolonged exposure may

S Graphic Arts

cause chronic effects.

OSHA regulatory status

This product is considered hazardous under 29 CFR 1910.1200 (Hazard

Communication).

Potential health effects

Eyes Causes eye irritation.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may

result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Target organs Blood. Central nervous system. Liver. Respiratory system.

Chronic effects Unconsciousness, Sterility, Liver injury may occur, May cause central nervous system

disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage. Can cause adverse reproductive effects. Pregnant women or women of child-bearing age

should not be exposed to this product.

Signs and symptoms Discomfort in the chest, Narcosis, Cyanosis, Liver enlargement, Jaundice, Defatting of the

skin. Irritation, Birth defects, Sterility.

 3. Composition / Information on Ingredients

 Components
 CAS #
 Percent

 Ethyl Alcohol
 64-17-5
 70 - 80

 n-Butane
 106-97-8
 15 - 20

 Propane
 74-98-6
 5 - 8

 Non-hazardous and other components below reportable levels
 0.1 - 1

4. First Aid Measures

First aid procedures

Skin contact

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Get medical attention if irritation develops or persists. Immediately take off all contaminated clothing. Wash off with warm water and soap. Get

medical attention if irritation develops or persists.

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Material name: Anti-Static Spray

Material ID: 713 Revision date: 14-NOV-2007 Print date: 14-NOV-2007

MSDS US

1/5

Ingestion

Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance, Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician

Symptoms may be delayed.

General advice

Call a physician if symptoms develop or persist.

# 5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition

sources and flash back.

Extinguishing media

Suitable extinguishing media

Foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor

nozzles; if this is impossible, withdraw from area and let fire burn.

Specific hazards

Fire may produce irritating, corrosive and/or toxic gases.

#### 6. Accidental Release Measures

Personal precautions

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel

away.

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

#### 7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Level 2 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.

#### 8. Exposure Controls / Personal Protection

# **Exposure limits**

	-	-	
Δ	1	м	ш

Components	CAS#	TWA	STEL	Ceiling	
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established	
n-Butane	106-97-8	1000 ppm	Not established	Not established	
Propane	74-98-6	1000 ppm	Not established	Not established	
OSHA					
Components	CAS#	TWA	STEL	Ceiling	
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established	
Propane	74-98-6	1000 ppm	Not established	Not established	

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye / face protection

Wear chemical goggles.

Skin protection

Protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

General hygeine considerations

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical & Chemical Properties

**Appearance** 

Compressed liquefied gas.

Color

clear colorless

Odor

Characteristic.

Physical state

Liquid.

Form Flammability (HOC) Aerosol.

29.51 kJ/g estimated

Flash back

**Pressure** 

43 - 53 psig @70F

Solubility Flash point Negligible -156 °F (-104.4 °C) estimated

**Boiling** point

127.4 °F (52.8 °C) estimated

Specific gravity

0.7163

pH

Not applicable

# 10. Chemical Stability & Reactivity Information

Chemical stability

Risk of ignition. Stable at normal conditions.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Isocyanates.

Hazardous decomposition products

May include oxides of nitrogen.

#### 11. Toxicological Information

Acute effects

Acute LD50: 2016 mg/kg estimated, Rat, Oral Acute LC50: 168 mg/l/4h estimated, Rat, Inhalation

Sensitization

Not expected to be hazardous by OSHA criteria.

Local effects

Liver toxicity. Blood disorder may occur after ingestion. Irritating to eyes. Components of

the product may be absorbed into the body through the skin.

Chronic effects

Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury. Prolonged exposure may cause chronic effects.

Blood disorder may occur after prolonged inhalation. Blood disorder may occur after

Subchronic effects **Neurological effects** 

prolonged skin contact. Hazardous by OSHA criteria.

Mutagenicity

Not expected to be hazardous by OSHA criteria.

Reproductive effects

Hazardous by OSHA criteria. Possible reproductive hazard. Can cause adverse

reproductive effects - such as birth defects, miscarriages, and infertility.

Teratogenicity

Not expected to be hazardous by OSHA criteria.

**Epidemiology** Further information Hazardous by OSHA criteria. Symptoms may be delayed.

# 12. Ecological Information

**Ecotoxicity** 

LC50 17281 mg/L estimated, Fish, 96.00 Hours, EC50 12306 mg/L estimated, Daphnia, 48.00 Hours,

Components of this product have been identified as having potential environmental

concerns.

### 13. Disposal Considerations

Waste codes

Material name: Anti-Static Spray

D001: Waste Flammable material with a flash point <140 F

Material ID: 713 Revision date: 14-NOV-2007 Print date: 14-NOV-2007

MSDS US

3/5

#### Disposal instructions

Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

#### 14. Transport Information

#### Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name

Consumer commodity

Hazard class

ORM-D

Subsidiary hazard class

None

Additional information:

Packaging exceptions

156, 306

Packaging non bulk

156, 306

Packaging bulk

None

#### IMDG

Basic shipping requirements:

Proper shipping name

AEROSOLS, flammable

Hazard class

2.1

**UN number** 

1950

Additional information:

Packaging exceptions

LTD QTY

Item Labels required 5F 2.1

**Transport Category** 

2

Basic shipping requirements:

Proper shipping name

Aerosols, flammable

Hazard class

2.1 1950

**UN number** Additional information:

Packaging exceptions

LTD QTY





4/5

#### 15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List,

CERCLA/SARA Hazardous Substances - Not applicable.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910,1200 hazardous

chemical

CERCLA (Superfund) reportable quantity

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** Delayed Hazard - Yes

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely

hazardous substance

Section 311 hazardous chemical Yes

MSDS US Material ID: 713 Revision date: 14-NOV-2007 Print date: 14-NOV-2007

Material name: Anti-Static Spray

#### Inventory status

Inventory name	On inventory (yes/no)*
Inventory of Existing Chemical Substances in China (IECSC)	No
European Inventory of New and Existing Chemicals (EINECS)	Yes
European List of Notified Chemical Substances (ELINCS)	No
Inventory of Existing and New Chemical Substances (ENCS)	No
Existing Chemicals List (ECL)	No
Toxic Substances Control Act (TSCA) Inventory	Yes
	Inventory of Existing Chemical Substances in China (IECSC) European Inventory of New and Existing Chemicals (EINECS) European List of Notified Chemical Substances (ELINCS) Inventory of Existing and New Chemical Substances (ENCS) Existing Chemicals List (ECL)

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

### State regulations

#### U.S. - Pennsylvania - RTK (Right to Know) List

Ethyl Alcohol 64-17-5 Present n-Butane 106-97-8 Present Propane 74-98-6 Present

#### 16. Other Information

**HMIS®** ratings

Health: 1\* Flammability: 3 Physical hazard: 0

Prepared by

Regulatory Compliance

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

Issue date

14-Nov-2007

Material name: Anti-Static Spray

Material ID: 713 Revision date: 14-NOV-2007 Print date: 14-NOV-2007