http://www2.hazard.com/msds/f2/bql/bqlmj.html

BEECHAM HOME IMPROVEMENT PRODUCTS INC -- DAP PAINTERS ACRYLIC LATEX CAULK -- 8030-00N035919

Product ID:DAP PAINTERS ACRYLIC LATEX CAULK MSDS Date:01/01/1988 FSC:8030 NIIN:00N035919 MSDS Number: BQLMJ === Responsible Party === Company Name: BEECHAM HOME IMPROVEMENT PRODUCTS INC Box: 277 City: DAYTON State:OH ZIP:45401 Country:US Info Phone Num: 513-253-7154 Emergency Phone Num: 513-253-7154 Preparer's Name:C.L. JOHNSON CAGE:1BL51 === Contractor Identification === Company Name: BEECHAM HOME IMPROVEMENT PRODUCTS INC Address:855 N 3RD ST Box:277 City:TIPP CITY State:OH ZIP:45371-3014 Country:US CAGE:1BL51 Company Name: DAP INC. Address:Box:277 City: DAYTON State:OH ZIP:45401-0277 Country:US Phone: 513-253-7154/800-543-3840 CAGE:90300 Ingred Name:ADDITIVES; (INERT ADDITIVES)

http://www2.hazard.com/msds/f2/bql/bqlmj.html (1 of 4)2/13/2008 3:07:48 PM

Ingred Name:NONHAZARDOUS INGREDIENTS
Fraction by Wt: 0%

Ingred Name:CALCIUM CARBONATE CAS:1317-65-3 RTECS #:EV9580000 OSHA PEL:15MG/M3 TDUST;5 RESP ACGIH TLV:10 MG/M3 TDUST

Ingred Name: ACRYLIC LATEX

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NONE KNOWN. Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER. Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:INHAL: NO KNOWN HLTH HAZ EXISTS. REMOVE TO FRESH AIR. SUPPORT BRTHG (GIVE O*2/ARTF RESP) . EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONTACT A PHYSICIAN. SKIN: WASH WITH S OAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION DEVELOPS. INGEST: GIVE LG AMOUNTS OF WATER & INDUCE VOMITING. CONTACT A PHYSICIAN.

Flash Point:NONFLAMMABLE
Extinguishing Media:FOAM, WATER, DRY CHEMICALS.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL

PROTECTIVE EQUIPMENT . USE WATER SPRAY TO COOL EXPOSED SURFACES. Unusual Fire/Explosion Hazard:NONE KNOWN.

Spill Release Procedures:SCRAPE/WIPE UP MATERIAL AND DISCARDED ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=============================== Handling and Storage Precautions: AVOID EXCESSIVE HEAT & FREEZING. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN. Other Precautions:NONE. ============== Respiratory Protection:NOT REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . Ventilation:NORMAL ROOM VENTILATION. Protective Gloves: IMPERVIOUS GLOVES . Eye Protection: CHEMICAL WORKERS GOGGLES . Other Protective Equipment:NOT REQUIRED. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER. ============================= HCC:N1 Spec Gravity:1.62(H*20=1) Evaporation Rate & Reference:NOT AVAILABLE Solubility in Water: SOLUBLE Appearance and Odor: WHITE PASTE WITH A MILD ODOR. Percent Volatiles by Volume: <25 Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid: EXCESSIVE HEAT. Hazardous Decomposition Products:NORMAL COMBUSTION PRODUCTS, I.E. OXIDES OF CARBON, OXIDES OF NITROGEN.

Waste Disposal Methods:PRODUCT IS NON-HAZARDOUS ACCORDING TO U.S. EPA'S HAZARDOUS WASTE MANAGEMENT REGULATIONS. DISPOSE OF IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS . http://www2.hazard.com/msds/f2/bql/bqlmj.html

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.