

VALVOLINE COMPANY -- SUPER HPO MOTOR OIL SAE 30W -- 9150-00N072289

=====
Product Identification
=====

Product ID: SUPER HPO MOTOR OIL SAE 30W

MSDS Date: 02/28/1996

FSC: 9150

NIIN: 00N072289

MSDS Number: CBXXG

=== Responsible Party ===

Company Name: VALVOLINE COMPANY

Box: 14000

City: LEXINGTON

State: KY

ZIP: 40512

Country: US

Info Phone Num: 606-357-7847

Emergency Phone Num: 800-274-5263

CAGE: J0366

=== Contractor Identification ===

Company Name: VALVOLINE COMPANY

Box: 14000

City: LEXINGTON

State: KY

ZIP: 40512

Country: US

Phone: 859-357-7206; EMERGENCY: 800-274-5263

CAGE: J0366

Company Name: VALVOLINE OIL CO

Address: 3499 BLAZER PKY

Box: 14000

City: LEXINGTON

State: KY

ZIP: 40512

Country: US

Phone: 606-357-7206 / 800-274-5263

CAGE: 72527

=====
Composition/Information on Ingredients
=====

Ingred Name: MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT-DEWAXED, HEAVY
PARAFFINIC (SEVERE SOLVENT-REFINING AND/OR (ING 2)

CAS: 64742-65-0

RTECS #: PY8038501

Fraction by Wt: SEE ING

OSHA PEL: N/K

ACGIH TLV: N/K

Ingred Name: ING 1: HYDROTREATMENT); (ALIPHATIC PETROLEUM DISTILLATES) %
(WT): 84.0-94.0

RTECS #: 9999999ZZ

Ingred Name: DETERGENT/DISPERSANT ENGINE OIL PACKAGE %(WT): 6.0-16.0

Fraction by Wt: SEE ING

OSHA PEL: N/K

ACGIH TLV: N/K

Ingred Name: PHOSPHORODITHOIC ACID, O-O-D1 C1-14-ALKYL ESTERS, ZINC
SALTS (2:1) (ZDDP); (ZINC COMPOUNDS)

CAS: 68649-42-3

Fraction by Wt: 1.1-1.1%

Ingred Name: FIRST AID PROC: VICTIM UNATTENDED. INHAL: IF SYMPS DEVELOP,
IMMED MOVE INDIVIDUAL AWAY FROM EXPOS & INTO FRESH (ING 6)

RTECS #:9999999ZZ

Ingred Name:ING 5:AIR. SEEK IMMEDIATE MEDICAL ATTENTION; KEEP PERSON WARM AND QUIET. IF PERSON IS NOT BREATHING, BEGIN (ING 7)

RTECS #:9999999ZZ

Ingred Name:ING 6:ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN.

RTECS #:9999999ZZ

Ingred Name:SPILL PROC:SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE, DIKE (ING 9)

RTECS #:9999999ZZ

Ingred Name:ING 8:AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON (ING 10)

RTECS #:9999999ZZ

Ingred Name:ING 9:SAND, CLAY, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

RTECS #:9999999ZZ

Ingred Name:HNDLG/STOR PREC:ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

RTECS #:9999999ZZ

Ingred Name:VENT:(GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW PEL/TLV (S).

RTECS #:9999999ZZ

Ingred Name:SUPDAT:OIL HAS BEEN SHOWN TO CAUSE SKIN CANCER IN LABORATORY ANIMALS CONTINUALLY EXPOSED BY RPTD APPLICATIONS. (ING 14)

RTECS #:9999999ZZ

Ingred Name:ING 13:AVOID PROLONGED OR REPEATED SKIN CONTACT.

RTECS #:9999999ZZ

==== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:EXPOS MAY CAUSE MILD EYE IRRIT. SYMPS MAY INCL STINGING, TEARING, & REDNESS. SKIN:EXPOS MAY CAUSE MILD SKIN IRRIT. PRLNG/RPTD EXPOS MAY DRY THE SKIN. SYMPS MAY INCL REDNESS, BURNING, DRYING & CRACKING, & SKIN BURNS. PRE-EXISTING SKIN DISORDERS MAY BE AGGRAVATED BY EXPOS TO THIS MATL. INGEST: (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:SINGLE DOSE ORAL TOX IS LOW. INGEST SMALL AMTS DURING NORM HNDL IS NOT LIKELY TO CAUSE HARMFUL EFTS; INGEST LRG AMTS MAY BE HARMFUL. INHAL:EXPOS IS POSS UNDER CERTAIN CNDTNS OF HNDLG & USE (FOR EXAMPLE, DURING HEATING, SPRAYING/STIRRING). SYMPS ARE MORE TYPICALLY SEEN AT AIR CONCS EXCEEDING (SUPDAT)

Medical Cond Aggravated by Exposure:PRE-EXISTING LUNG DISORDERS, E.G. ASTHMA-LIKE CONDITIONS, MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

==== First Aid Measures =====

First Aid:EYES:MOVE INDIVIDUAL AWAY FROM EXPOS & INTO FRESH AIR. FLUSH EYES GENTLY W/H*20 WHILE HOLDING EYELIDS APART. IF SYMPS PERSIST/THERE IS ANY VISUAL DEFCLT, SEEK MED ATTN. SKIN:REMOVE CONTD

CLTHG. WASH EXPOSED AREA W/SOAP & H*2O. IF SYMPS PERSIST, SEEK MED ATTN. LAUNDRER CLTHG BEFORE REUSE. INGEST:DO NOT INDUCE VOMIT. GIVE ONE GLASS OF MILK/H*2O, & GET MED ATTN IMMED. IF POSS, DO NOT LEAVE (ING 5)

===== Fire Fighting Measures =====

Flash Point:430F,221C
Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:USE NIOSH APPRVD SCBA & FULL PROT EQUIP .
WATER/FOAM MAY CAUSE FROTHING WHICH CAN BE VIOLENT & POSSIBLY ENDANGER THE LIFE OF THE FIREFIGHTER. (SUPDAT)
Unusual Fire/Explosion Hazard:NEVER USE WELDING/CUTTING TORCH ON/NEAR DRUM (EVEN EMPTY) BECAUSE PROD (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY. DENSE SMOKE MAY BE GENERATED WHILE BURNING.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL:ABSORB LIQ ON VERMICULITE, FLOOR ABSORB/OTHER ABSORB MATL. LRG SPILL:PVNT RUN-OFF TO SEWERS, STREAMS/OTHER BODIES OF H*2O. IF RUN-OFF OCCURS, NOTIFY PROPER AUTH AS REQ, THAT A SPILL HAS OC CURED. PERSONS NOT WEARING PROT EQUIP (ING 8)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), (ING 11)
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE. HOWEVER, IF OIL MISTS ARE GENERATED ABOVE RECOMMENDED PEL/TLV OF 5 MG/M3, THEN A NIOSH APPROVED RESP IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. (CONSULT YOUR INDUSTRIAL HYGIENIST.)
Ventilation:NOT REQD UNDER NORM CNDTNS OF USE. HOWEVER, IF UNUSUAL OPERATING CNDTNS EXIST, THEN PROVIDE SUFFICIENT MECH (ING 12)
Protective Gloves:NITRILE RUBBER GLOVES.
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .
Other Protective Equipment:EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA . WEAR NORMAL WORK CLTHG COVERING ARMS & LEGS.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
FIRE FIGHT PROC:REFER TO THE PERSONAL PROT EQUIP SECTION OF THIS MSDS.
EFTS OF OVEREXP:THE REC EXPOS LIM. SYMP OF EXPOS: GI IRRIT (NAUSEA, VOMIT, DIARR), IRRIT (NOSE, THROAT, RESP TRACT) (PRE-EXISTING LUNG DISORDERS, E.G. ASTHMA-LIKE CNDTNS, MAY AGGRAVATED BY EXPOS TO THIS MATERIAL), ABDOMINAL PAIN. USE MOTOR (ING 13)

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>425F,>218C
Vapor Density:N/K
Spec Gravity:0.891 @ 60.00F
Solubility in Water:NONE SPECIFIED BY M.
Appearance and Odor:DRY, CLEAR & BRIGHT. STATE: LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH: STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:MAY FORM: CARBON DIOXIDE AND CARBON MONOXIDE, OXIDES OF SULFUR, NITROGEN AND PHOSPHORUS, VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.