# MATERIAL SAFETY DATA SHEET

### SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: DE-SOLVE

ID NUMBER: LB735

PRODUCT USE/CLASS: POWDERED DRAIN OPENER

MANUFACTURER: LUBAR CHEMICAL

1700 CAMPBELL

KANSAS CITY, MO 64108

EMERGENCY TELEPHONE:816-234-3000

PREPARED BY: TERRY HALL

PHONE: 816-471-2560

PREPARE DATE: 11/09/99

## SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NUMBER	WT.PERCENT IS LESS THAN	TLV-TWA	TLV-STEL	PEL-TWA	SKIN DESIGNATION
SODIUM HYDROXIDE	1310-79-2	99.0 %	NO INFO	NO INFO	YES	

(See Section 11 for abbreviation legend)

#### SECTION III - PHYSICAL DATA

BOILING RANGE: N.A.

VAPOR DENSITY: Is heavier than air

ODOR: CITUR

SPECIFIC

GRAVITY: 0.0000

APPEARANCE: YELLOW POWDER

COMPLETE

EVAPORATION RATE: Is slower than Ether

SOLUBILITY IN H2O:

(See Section XI for abbreviation legend)

# SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N.A.

LOWER EXPLOSIVE LIMIT: N.A.

UPPER EXPLOSIVE LIMIT:

N.A.

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: EXTINGUISH ALL NEARBY SOURCES OF IGNITION SINCE FLAMMABLE HYDROGEN GAS WILL BE LIBERATED FROM CONTACT WITH SOME METALS (ALUMINUM, MAGNESIUM, ETC.). CAUSTICS WILL REACT WITH MANY ORGANIC CHEMICALS. CONTACT WITH WATER MAY GENERATE HEAT WHICH COULD IGNITE COMBUSTIBLES.

SPECIAL FIREFIGHTING PROCEDURES: FIREFIGHTERS SHOULD WEAR SELF CONTAINED

BREATHING APPARATUS AND PROTECTIVE CLOTHING. MATERIAL IS NON-COMBUSTIBLE, USE EXTINGUISING MEDIA AS APPROPRIATE TO SURROUNDING MATERIALS.

# SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - EYE CONTACT: DESTRUCTIVE. MAY IRRITATE OR BURN, BURNS COULD CAUSE BLINDNESS.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: DESTRUCTIVE, OVEREXPOSURE MAY PRODUCE BURNS.

EFFECTS OF OVEREXPOSURE - INHALATION: EXCESSIVE INHALATION MAY DAMAGE RESPIRATORY TRACT. POSSIBLE NAUSEA, DIZZINESS, DIFFICULT BREATHING.

EFFECTS OF OVEREXPOSURE - INGESTION: EXTREMELY CORROSIVE. LARGE QUANTITIES COULD CAUSE SEVERE PAIN, NAUSEA, DEATH.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: RESPIRATORY SENSITIVITY. DERMATITIS, ALLERGIC RESPONSES.

FIRST AID - EYE CONTACT: FLUSH WITH WATER 15-30 MINUTES, LIFTING EYELIDS. GET MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: FLUSH WITH WATER 15 MINUTES. REMOVE CONTAMINATED CLOTHING. LAUNDER BEFORE REUSE. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

FIRST AID - INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION, GET MEDICAL ATTENTION.

FIRST AID - INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE LOTS OF WATER OR MILK, THEN DRINK DILUTED VINEGAR, LEMON JUICE. GET MEDICAL ATTENTION.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION INGESTION EYE CONTACT

(Continued on Page 2)

ID NUMBER: LB735

Preparation Date: 12/23/99

Page 2

## SECTION VI - REACTIVITY DATA

HAZARDOUS DECOMPOSITION PRODUCTS: NORMAL DECOMPOSITION TO CARBON DIOXIDE (CO2), CARBON MONOXIDE (CO). CO MAY BE HAZARDOUS IN ENCLOSED HIGH CONCENTRATIONS.

CONDITIONS TO AVOID: ACIDS.

INCOMPATABILITY: ACTIVE METALS. STRONG ACIDS MAY PRODUCE VIOLENT REACTION.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

#### SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WEAR APPROPRIATE PROTECTIVE AND RESPIRATORY EQUIPMENT. PREVENT SPILLS FROM ENTERING SEWERS, OR ANY UNAUTHORIZED WATER SYSTEMS.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH APPROPRIATE FEDERAL, STATE AND LOCAL REGULATIONS.

#### SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: NIOSH/OSHA APPROVED RESPIRATOR TYPES SUITABLE FOR MATERIALS IN SECTION II RECOMMENDED. APPROVED CHEMICAL/MECHANICAL FILTERS RECOMMENDED WHEN VENTILATION IS RESTRICTED.

VENTILATION: SUFFICIENT VENTILATION, IN VOLUME AND PATTERN, SHOULD BE PROVIDED TO KEEP AIR CONTAMINATION BELOW CURRENT APPLICABLE OSHA PERMISSIBLE EXPOSURE LIMIT OR ACGHI'S TLV LIMIT.

SKIN PROTECTION: HEAVY RUBBER GLOVES NEEDED.

EYE PROTECTION: SAFETY GLASSES OR GOGGLES.

OTHER PROTECTIVE EQUIPMENT: PREVENT PROLONGED CONTACT. WEAR BOOTS AND IMPERVIOUS CLOTHING IF NECESSARY. EYE WASH, SAFETY SHOWER AVAILABLE.

HYGENIC PRACTICES: WASH AFTER EACH USE.

## SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: KEEP CONTAINERS TIGHTLY CLOSED. MATERIAL IS HYGROSCOPIC AND WILL PICK UP MOISTURE FROM THE AIR.

OTHER PRECAUTIONS: OBEY ALL HAZARD WARNINGS WHEN CONTAINERS ARE EMPTIED. KEEP CONTAINERS CLOSED.

SECTION X - HMIS RATINGS

HMIS RATINGS HEALTH: 3

FLAMMABILITY: 0

REACTIVITY: 2

### SECTION XI - OTHER REGULATIONS

SARA SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER

WT/WT %

No SARA Section 313 components exist in this product.

PREVIOUS MSDS REVISION DATE: 11/17/97

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS is been checked and should be accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.