# **Material Safety Data Sheet**

Section 1: Product & Company Identification

**Product Name:** 

**Lithium General Purpose Grease** 

Product Number (s):

SL3310, SL3311, SL3315, SL3317, 8SL3310

Manufactured By:

CRC Industries, Inc. 885 Louis Drive

Warminster, PA 18974 www.crcindustries.com

General Information Technical Assistance (215) 674-4300 (800) 521-3168

**Customer Service** 

(800) 272-8963

24-Hr Emergency (CHEMTREC)

(800) 424-9300

## Section 2: Hazards Identification

#### **Emergency Overview**

Appearance & Odor: Amber semi-solid to solid grease with a faint petroleum odor

As defined by OSHA's Hazard Communication Standard, this product is nonhazardous.

#### Potential Health Effects:

EYE:

May cause irritation.

SKIN:

Repeated or prolonged contact can result in drying of the skin.

INHALATION:

Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low

volatility of this product.

INGESTION:

Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into

the lungs and subsequent pneumonitis.

CHRONIC EFFECTS:

Unknown

TARGET ORGANS:

None known

Medical Conditions Aggravated by Exposure:

Skin or respiratory conditions

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Number (s): SL3310, SL3311, SL3315, SL3317, 8SL3310

## Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.	
Refined heavy naphthenic distillates	64741-96-4 / 64742-52-5	85 - 95	
Lithium 12-hydroxystearate	7620-77-1	3 – 7	

#### Section 4: First Aid Measures

Eye Contact:

Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact:

Remove contaminated clothing and wash affected area with soap and water. Call a physician

if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation:

Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion:

Do not induce vomiting. Seek medical attention.

Note to Physicians:

Treat symptomatically.

## Section 5: Fire-Fighting Measures

Flammable Properties:

This product is nonflammable.

Flash Point:

450 F (COC)

Upper Explosive Limit:

ND

Autoignition Temperature:

ND

Lower Explosive Limit:

ND

Suitable Extinguishing Media:

CO2, dry chemical, sand, dolomite, alcohol resistant foam, water spray

Products of Combustion:

Oxides of carbon

Protection of Fire-Fighters:

Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed

containers cool and to knock down vapors which may result from product

decomposition. Avoid water in straight hose stream as it will scatter and spread fire.

#### Section 6: Accidental Release Measures

Personal Precautions:

Use personal protection recommended in Section 8. Minimize skin contact.

**Environmental Precautions:** 

Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains. Advise authorities if product has entered waterways.

Methods for Containment & Clean-up:

Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using

Product Number (s): SL3310, SL3311, SL3315, SL3317, 8SL3310

an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

#### Section 7: Handling and Storage

Handling Procedures:

Keep container away from heat, sparks, and open flame. High temperatures may produce

irritating vapors. Eye wash station should be available at work place. Keep containers

closed when not in use. Ventilate well, especially in warmer environments.

Storage Procedures:

Store in a cool dry area out of direct sunlight. Store separated from acids and oxidizing

materials. Store away from sparks and open flame.

Aerosol Storage Level:

NA

## Section 8: Exposure Controls/Personal Protection

#### **Exposure Guidelines:**

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURC E	UNIT
Refined naphthenic distillate	5*	NE	5*	10*	NE		mg/m <sup>3</sup>
Lithium 12-hydroxystearate	NE	NE	NE	NE	NE		
N.E. – Not Established	(c) - ceiling (s) - skin (v) - vacated * - oil mist						

**Engineering Controls:** 

Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation

of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure

guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection:

None required for normal work where adequate ventilation is provided. Use NIOSHapproved self-contained positive pressure respirators in low circulation areas and for

emergencies.

Eye/face Protection:

For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection:

Use protective gloves such as neoprene or nitrile. Also , use full protective clothing if there

is prolonged or repeated contact of liquid with skin.

## Section 9: Physical and Chemical Properties

Physical State:

semi-solid grease

Color:

amber

Odor:

mild petroleum

Specific Gravity:

0.90 @ 60 F

Initial Boiling Point:

ND

Freezing Point: ND

Vapor Pressure: < 0.1 mmHg @ 68 F Vapor Density:

> 5

(air = 1)

Evaporation Rate: < 0.01

(butyl acetate = 1)

Product Number (s): SL3310, SL3311, SL3315, SL3317, 8SL3310

Solubility:

Insoluble in water

pH: NA

Volatile Organic Compounds:

wt %:

< 0.1

g/L: < 0.9

lbs./gal:

< 0.01

## Section 10: Stability and Reactivity

Stability:

Stable

Conditions to Avoid:

Heat

Incompatible Materials:

Avoid contact with acids and oxidizing substances.

Hazardous Decomposition Products:

Oxides of carbon

Possibility of Hazardous Reactions:

No

## Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

#### **ACUTE EFFECTS**

Component	Test	Result	Route	<u>Species</u>
Naphthenic distillates	LD50	> 5000 mg/kg	Oral	Rat
Naphthenic distillates	LD50	> 2000 mg/kg	Dermal	Rabbit
Naphthenic distillates	LC50	2.18 mg/L/4H	Inhalation	Rat

#### CHRONIC EFFECTS

Carcinogenicity:

Component

None listed

OSHA: IARC:

None listed

NTP:

None listed

Mutagenicity:

None available

Other:

Naphthenic distillates

Base oils of this product contain < 3% DMSO Extractable total

polycyclic aromatic compound (PAC) per IP 346.

## Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Result

Ecotoxicity:

Naphthenic distillates: 48 Hr EC50 Daphnia magna: >1000 mg/L

Persistence / Degradability:

None available

Bioaccumulation / Accumulation:

None available

Mobility in Environment:

None available

Product Number (s): SL3310, SL3311, SL3315, SL3317, 8SL3310

## Section 13: Disposal Considerations

Disposal:

This product is not a RCRA hazardous waste.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

#### Section 14: Transport Information

Proper shipping description:

US DOT (ground):

Not Regulated

Special Provisions:

None

## Section 15: Regulatory Information

#### U.S. Federal

#### Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

#### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients:

None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

#### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:

Fire Hazard

No

Reactive Hazard

No

Release of Pressure

No

Acute Health Hazard Chronic Health Hazard No No

Section 313 Toxic Chemicals:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 and 40 CFR Part 372:

None

#### Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

#### State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

Product Number (s): SL3310, SL3311, SL3315, SL3317, 8SL3310

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

NONE

#### State Right to Know:

New Jersey: Pennsylvania: None

Massachusetts:

None

Rhode Island:

None None

Additional Regulatory Information:

None

#### Section 16: Other Information

NFPA: HMIS:

Health: 1

Health: 1

Flammability: 1 Flammability: 1 Reactivity:

Reactivity: 0

PPE: В

Prepared By:

Michelle Rudnick

CRC #:

2020

Revision Date:

9/21/2006

Changes since last revision:

MSDS reformatted in accordance with ANSI Z400.1-2004

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:

Chemical Abstract Service

NA:

Not Applicable Not Determined

ppm: TCC:

Parts per Million Tag Closed Cup

ND: NE:

Not Established grams per Liter

PMCC: PPE:

Pensky-Martens Closed Cup Personal Protection Equipment g/L: lbs./gal: STEL:

pounds per gallon

TWA: OSHA: Time Weighted Average Occupational Safety and Health Administration

COC:

Short Term Exposure Limit Cleveland Open Cup

ACGIH NIOSH American Association of Governmental Industrial Hygienists

National Institute of Occupational Safety & Health